

Excel Packaging Systems, Inc.

Add: 11799 Jersey Blvd, Rancho Cucamonga, CA 91730

Tel: 1-909-476-1100 Fax: 1-909-923-1313

E-mail: info@excelpackagingequipment.com

PP-1230R-143 Semi-Auto Label Shrink Tunnel



FEATURES

- PP-1230R-143 Semi-Auto Label Shrink Tunnel is mainly for bottle shaped, jars, goblet product labels shrink which can shrink the bottle neck, body, bottom and overall;
- The frequency inverter controls transmission speed and has variable speed;
- The shrinking temperature is intelligently controlled by digital temperature controller and can be adjusted;
- The molds can rotate 360 degrees to ensure smooth transportation;
- The conveyor with protective cover to avoid the operator's fingers get caught in the moving parts, so that it can pass CE safety standards;
- The bottle nipping stations can be adjusted without changing the molds;
- Adopt double hot air circulation system;
- It is widely used in food, pharmaceuticals. Cosmetics and other industries.

Model	PP-1230R-143
Power	12kw
Power Supply	AC 220V/380V 3PH 50/60Hz
Max Packing Size Dia.×H	120×280mm (4.7"x11")
Tunnel Size L×W×H	1250×200×400mm (49.5"x7.8"x 15.75")
Packing Speed	20-40m/min
Shrink Film	PET/PVC
Machine Size L×W×H	3640×520×1400mm (143"x20.5"x55.1")
Table Height	520±50mm
G./N. Weight	480/450kgs
Air Temperature	0-300℃

CONFIGURATION

Shrink Tunnel	Brand	Country
Gear Motor	GPG	Taiwan
Circulation Motor	SURFON	Taiwan
Intermediate Relay	Siemens	Germany
Temperature Controller	Autonics	Korea
Electrical Breaker	Schneider	France
Thermal Overload Relay	Schneider	France
AC Contractor	Schneider	France
Frequency Inverter	Schneider	France
Switches	Siemens	Germany

LAYOUT

