

Tabletop Wrap Around Labeling Machine

Model:

PP-530

An efficient, portable, wrap around labeler ideal for small runs.



Example of wrap around label application.

◆ EASY TO USE

The Delta HMI interface makes it easy to use the PP-530. Simple hand wheel adjustments make for quick set-up and fast changeover time keeping the machine online with less downtime.

◆ LOW MAINTENANCE

Manufactured to (GMP) standards, the PP-530 are made of **#304 stainless steel and anodized aluminum**, and designed to be used in harsh working environments where other equipment might fail. The Preferred Pack® machine is the right choice for the discriminating buyer.

◆ SIMPLE DESIGN

Built into all Preferred Pack® designed labeling machines is a cost effective solution to fast, reliable, pressure-sensitive labeling for all types of round containers and bottles.

PERFORMANCE

- The preset counter means the machine automatically stops once the preset quantity of products has been labeled.
- The product counter lets you precisely track the amount of labels applied at any point during the production run.
- The PP-530 feature a Delta PLC Touchscreen HMI control system that maintains default settings and memory locations.

EFFICIENT

- The digital label adjust position allows the operator to set the desired position of the label to the package with just one touch.
- The missing label feature locates missing labels on the roll stock, and shuts the machine down if one is found. This ensures each product is labeled correctly.

ADJUSTABLE

- The standard Delta Touchscreen HMI with 83 program memory and label sensors can be easily adjusted for a wide variety of labeling applications. With the digital position setting, your labels are placed accurately on the product every time.
- The PP-530 offer an optional hot-stamp ribbon printer which can easily be installed should the need arise. This optional feature lets printers work in sync with the labeler to ensure accurate code placement.
- Designed to be used for in-line automatic or semi-automatic applications.

SENSIBLE

- The PP-530 is compact, portable and can be conveniently moved to other production areas, allowing for changes in production or products.
- All labelers are made of **304 stainless steel and anodized aluminum**. This extremely durable metal is specially treated to guard against rusting and other effects from harsher environments.

PRECISE

- The PP-530's stepper motor label position setting allows the operator to accurately set the label position, ensuring fast, accurate label delivery.
- The PP-530's controls are all in sync, making sure that all components run at the same speed.

COMPLIANT

- All Preferred Pack® labelers are manufactured in compliance with Good Manufacturing Practice (GMP) standards.
- On/Off switch and Emergency Stop Switch are prominently located on the main control panel.



Example of wrap around label application.

Maximum Dispensing Speed	80'/minute, (25m/minute)
Maximum Conveyor Speed	80'/minute, (25m/minute)
Dimensions L-W- H	43.3" x 34.3" x 20" (1100mm x 870mm x 508mm)
Label Width	.39" - 4.75" (10mm - 120mm)
Bottle Diameter	.78" - 4.75" (20mm - 120mm)
Conveyor Width	6" (150mm)
Spool Diameter	10" (254mm)
Inner Core	3" (76mm)
Label Accuracy	+/- 1mm
Voltage	110 VAC 50 HZ 1 Phase
Net Weight	Approx 165 lbs (75 kgs)