



OVERVIEW

The S-5547 is a High Speed, Servo Driven Flow Wrapper with speeds from 30-150ppm with the Single Jaw and 200PPM with the optional Dual Jaw.

STANDARD FEATURES


- Servo Drive Seal Head
- 7ft Flighted Infeed
- Photo Eye for Print Registration
- Siemens PLC and HMI Color Touch Screen
- Store Up to 50 Recipes
- Adjustable Forming Box



7" Color Touch-Screen
HMI w/ 50 Program
Memory



7ft. Flighted Infeed
with Product Carriers



Upper Brush Pushes
Air Out of the Bag



Discharge Brush Helps
Separate Products



Adjustable Forming Box



24" Long Discharge
Conveyor

Horizontal Servo Flow Wrapping Machine

S-5547

| Model # | Speed | Bag Length | Max Film Width | Max Product Width | Max Product Height | Power | Air |
|---------------|-----------|-----------------|----------------|-------------------|------------------------|--------------------|---------------|
| S-5547 | 30-250ppm | 3.5" to 15.7" | 18.5" | 7.5" | 1.18" or 2.36" or 3.5" | 220V, 1 Ph, 10 AMP | 1cfm @ 80 psi |
| S-5561 | 20-170ppm | 5.11" to 17.71" | 24" | 10.4" | 1.18" or 2.36" or 3.5" | 220V, 1 Ph, 10 AMP | 1cfm @ 80 psi |
| S-5571 | 20-170ppm | 5.11" to 17.71" | 28" | 13" | 1.18" or 2.36" or 3.5" | 220V, 1 Ph, 10 AMP | 1cfm @ 80 psi |

OPTIONS

- #304 Stainless Steel Frame
- Videojet Thermal Transfer Printer
- Label Applicator
- Dual Seal Jaws for Increased Speed



#304 Stainless Steel Frame

TECHNICAL DRAWING

