

Horizontal Wrap Around Labeling System

Model:

PP-613

A dependable wrap around system for labeling small, round containers laying down.



Shown with optional Hot Stamp Ribbon Printer

◆ EASY TO USE

The Delta HMI interface makes it easy to use the PP-613. Simple hand wheel adjustments make for quick set-up and fast changeover time keeping the machine online with less downtime.

◆ LOW MAINTENANCE

Manufactured to (GMP) standards, the PP-613 are made of **#304 stainless steel and anodized aluminum**, and designed to be used in harsh working environments where other equipment might fail. The Preferred Pack® machine is the right choice for the discriminating buyer.

◆ SIMPLE DESIGN

Built into all Preferred Pack® designed labeling machines is a cost effective solution to fast, reliable, pressure-sensitive labeling for small, round items.

PERFORMANCE

- The preset counter means the machine automatically stops once the preset quantity of products has been labeled.
- The product counter lets you precisely track the amount of labels applied at any point during the production run.
- The PP-613 feature a Delta PLC Touchscreen HMI control system that maintains default settings and memory after the machine has been idle for a period of time.

EFFICIENT

- The digital label adjust position allows the operator to set the desired position of the label to the package with just one touch.
- The missing label feature locates missing labels on the roll stock, and shuts the machine down if one is found. This ensures each product is labeled correctly.

ADJUSTABLE

- The standard Delta Touchscreen HMI with 83 program memory and label sensors can be easily adjusted for a wide variety of labeling applications. With the digital position setting, your labels are placed accurately on the product every time.
- The PP-613 offer an optional hot-stamp ribbon printer which can easily be installed should the need arise. This optional feature lets printers work in sync with the labeler to ensure accurate code placement.
- Designed to be used for in-line automatic or semi-automatic applications.

SENSIBLE

- The PP-613 come with casters and can be conveniently moved to other production areas, allowing for changes in production or products.
- All labelers are made of **304 stainless steel and anodized aluminum**. This extremely durable metal is specially treated to guard against rusting and other effects from harsher environments.
- Height-adjustable label applicator head makes it easy to match product heights.

PRECISE

- The PP-613's stepper motor label position setting allows the operator to accurately set the label position, ensuring fast, accurate label delivery.
- The PP-613's controls are all in sync, making sure that all components run at the same speed.

COMPLIANT

- All Preferred Pack® labelers are manufactured in compliance with Good Manufacturing Practice (GMP) standards.
- On/Off switch and Emergency Stop Switch are prominently located on the main control panel.



Example of wrap around label application.

| | |
|---------------------------|---|
| Maximum Dispensing Speed | 80'/min (25m/min) |
| Maximum Conveyor Speed | 80'/min (25m/min) |
| Dimensions L-W- H | 78" x 42" x 64" (1981mm x 1067mm x 1626mm) |
| Maximum Label Size W-L | 6" x 3" (152mm x 75mm) |
| Bottle Diameter | 0.3" – 1" (7.6mm - 25mm) |
| Range of Container Length | 0.25" – 6" (6.5mm – 152mm) |
| Conveyor Width | 4" (102mm) |
| Spool Diameter | 14" (356mm) |
| Inner Core | 3" (76mm) |
| Voltage | 110VAC, 50/60 HZ, 1 Phase |
| Drive | Stepper Motor |
| Net Weight | Approx 385 lbs (175 kgs) |