

Side Apply Labeler with Corner Wrap

Model:

PP-625J

For labeling the side and wrapping around the corner of a container



◆ EASY TO USE

The Delta HMI interface makes it easy to use the PP-625J. Simple hand wheel adjustments make for quick set-up and fast changeover time keeping the machine online with less downtime.

◆ LOW MAINTENANCE

Manufactured to (GMP) standards, the PP-625J are made of **#304 stainless steel and anodized aluminum**, and designed to be used in harsh working environments where other equipment might fail. The Preferred Pack® machine is the right choice for the discriminating buyer.

◆ SIMPLE DESIGN

Built into all Preferred Pack® designed labeling machines is a cost effective solution to fast, reliable, pressure-sensitive labeling for trays, boxes, chipboard containers, bags and even caps on bottles.

PERFORMANCE

- The preset counter means the machine automatically stops once the preset quantity of products has been labeled.
- The product counter lets you precisely track the amount of labels applied at any point during the production run.
- The PP-625J feature a Delta PLC Touchscreen HMI control system that maintains default settings and memory after the machine has been idle for a period of time.

EFFICIENT

- The digital label adjust position allows the operator to set the desired position of the label to the package with just one touch.
- The missing label feature locates missing labels on the roll stock, and shuts the machine down if one is found. This ensures each product is labeled correctly.

ADJUSTABLE

- The standard Delta Touchscreen HMI with 83 program memory and label sensors can be easily adjusted for a wide variety of labeling applications. With the digital position setting, your labels are placed accurately on the product every time.
- The PP-625J offer an optional hot-stamp ribbon printer which can easily be installed should the need arise. This optional feature lets printers work in sync with the labeler to ensure accurate code placement.
- Designed to be used for in-line automatic or semi-automatic applications.

SENSIBLE

- The PP-625J come with casters and can be conveniently moved to other production areas, allowing for changes in production or products.
- All labelers are made of **304 stainless steel and anodized aluminum**. This extremely durable metal is specially treated to guard against rusting and other effects from harsher environments.
- Height-adjustable conveyor makes it easy to match production line heights.

PRECISE

- The PP-625J's stepper motor label position setting allows the operator to accurately set the label position, ensuring fast, accurate label delivery.
- The PP-625J's controls are all in sync, making sure that all components run at the same speed.

COMPLIANT

- All Preferred Pack® labelers are manufactured in compliance with Good Manufacturing Practice (GMP) standards.
- On/Off switch and Emergency Stop Switch are prominently located on the main control panel.



Example of corner wrap label application.

Maximum Dispensing Speed	131.2'/min (40m/min)
Maximum Conveyor Speed	80/min (25m/min) *optional customization
Dimensions L-W- H	60" x 30" x 41" (1524mm x 762mm x 1041mm)
Maximum Label Width	5" (130mm)
Maximum Container Width	10" (250mm)
Conveyor Belt Width	10" (250mm)
Conveyor Length	55" (1400mm)
Spool Diameter	14" (356mm)
Inner Core	3" (76mm)
Voltage	110 VAC 50/60 HZ 1 Phase
Drive	Stepper Motor
Net Weight	Approx. 330 lbs (150 kgs)