Vertical, Free Standing, Coding

CONTINUOUS BAND SEALERS

Model:

PP-1120LD

PP-1120LD *is suitable for sealing all types of thermoplastic materials and bags. The vertical configuration is ideal for sealing stand up pouches and liquid-type products. This sealer can be used in a variety of fields such as the food, medical, and cosmetic industries.* ***PP-1120LD*** *is equipped with an adjustable sealing head and conveyor suitable providing a wide range of bag heights.* ***PP-1120LD*** *utilizes dry ink coding to print numbers or letters on the seal line.*

FEATURES

- *Durable stainless steel construction*
- *Easy to operate - minimal operator training*
- *Fast warm up time*
- *Ideal for medium duty and heavy duty applications*
- *Vertical configuration makes this suitable for any product including liquids*
- *Solid state digital temperature controller that maintains the seal bars at a proper temperature for consistent seal quality*
- *Motorized rubber conveyor for speed control*
- *Knurled pressure wheels with variable pressure adjustment*
- *Sealing method - constant/direct heat accompanied with a pair each of cooling and heating blocks*
- *Fully adjustable conveyor (both height and depth of conveyor in relation to seal bars can be adjusted)*
- *Dry ink coding allows for printing at the seal line*
- *Unit feeds from Right to Left*
- *Spare parts includes: PC Board, PTFE belt, wheel belt, fuse, motor brush, heating element, silica gel ring, silicone pin, and type set*

SPECIFICATIONS	
UNIQUE FEATURES	ADJUSTABLE SEALING HEAD
FEEDING	RIGHT TO LEFT
POWER	110V / 60Hz
MOTOR POWER	230 (1/3 HP)
SEALING SPEED	0-394 INCHES/MINUTE
SEAL WIDTH	8MM
TEMPERATURE RANGE	0-300°C
SEALING POWER	300 X 2
CONVEYOR SIZE	55" x 10"
SINGLE CONVEYOR LOAD	11LBS
MAX CONVEYOR LOAD	33LBS
BAG SIZE (FILLED)	**3.9" – 27.0"**
DISTANCE FROM CONVEYOR TO FLOOR	19.6" – 41.3"
CHARACTER SIZE (FOR PRINTING VERSION – FRM-1120AL/D)	TWO TYPES AVAILABLE R-TYPE: PT 18PT – 2 LINES OPTION: PT 10.5 – 3 LINES
PRINTING HEATING POWER (W)	40 x 2
PRINTING OPTIONS	20 CHARACTERS/LINE
DIMENSIONS	57" X 27" X 58"
SHIPPING DIMENSIONS	62" X 28" X 68"
WEIGHT	344 LBS / 450 (GW)