

Incline Discharge Conveyor

Model

INC-52

Description

Will convey a wide variety of products such as confections, noodles, chocolates, frozen meats etc. Built to order with seamless integration to upstream and/or downstream equipment. The conveying speed can be adjusted from 0-60 FPM to maximize performance.

Features

- Stainless Steel Construction
- Plastic Intra-lox Type Belt
- Variable Speed Drive
- Food Grade Belting
- 220 volt, 1 Phase, 50/60 Hz
- Available in 10, 12, 18 and 24 inch widths

Options

- IP-54 Wash Down Motor
- Polypropylene Side Guides (both sides)



Easily fits under any vertical bagger



220 Volt Variable Speed Drive Motor



Adjustable height legs from 39" to 42"



1" tall cleats spaced 10" apart help transport products up the conveyor

Model #	INC-52-10	INC-52-12	INC-52-18	INC-52-24
Conveyor Width	10"	12"	18"	24"
Infeed Height	6.5"	6.5"	6.5"	6.5"
Power	0.75 kw	0.75 kw	0.75 kw	0.75 kw
Voltage	220 Volt	220 Volt	220 Volt	220 Volt
Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel

Preferred Pack®

The Industry Standard for
Quality and Reliability