

Shrink Tunnel

Model:

PP1808-44

General purpose machine for a wide variety of applications.

Standard Features Include:


- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Control 0-400°
- Adjustable Air Velocity Control
- State-of-the-Art AC Variable Speed Drive 0-75 FPM
- Chromed Conveyor Rollers and Shaft (No Rust)
- Automatic Tunnel Cool Down with Shut Off
- 1HP Blower Motor
- Sealed Bearings on Drive and Idler Shafts
- Chamber Size 18"W x 8"H x 44"L
- Quietest Tunnel on the Market
- Heats up to 300° F in less than 15 minutes
- Thermal Overload Protection on All Motors
- Locking Casters
- Adjustable Leveling Pads 32" - 36.5"
- Anti-Jam Safety Features on Conveyor
- 9 KW Heater Bank
- 2 year warranty



The **PP1808-44 Tunnel** is a great general purpose shrink tunnel that can be used for a wide variety of applications. Can be used with shrink bands, neck bands, full body sleeves, used with shrink film, used as drying or curing tunnel etc.

Available Options:

- 12" and 16" Tunnel Opening
- Close Roller Spacing 1/2" Gap
- Teflon Mesh Belt
- Stainless Steel Metal Mesh Belt



Falcon Belting



Teflon Mesh Belting



Stainless Steel Metal Mesh Belting



High Density Rollers - Close Roller Spacing 1/2" Gap



Shrink Tunnel

PP1808-44



Variable Air Velocity



Variable Speed Control
0 - 75 FPM



Digital Temperature Control



Lighted Viewing Window



Adjustable Leveling Pads



PP1812-44 and PP1816-44
Available for Taller Package Sizes



* Stainless Steel Frame
Construction Available

Specifications:

MODEL	VOLTS	POWER		WEIGHT	TUNNEL OPENING			SPEED
		PHASE	AMPS		L	W	H	
PP1808-44	220	1	40	450	44	18	8	0-75 FPM
PP1812-44	220	1	40	470	44	18	12	0-75 FPM
PP1816-44	220	1	40	495	44	18	16	0-75 FPM

