

# Pallet Stretch Wrappers

*A low-cost, entry level, semi-automatic machine.*

Model:

## PP-982 Series

### PP-982 HP High Profile

\*does not include ramp



**NEW MODEL!**  
Electro Mechanical  
Brake Stretch with  
HMI Touch Screen

### PP-982 LP Low Profile



### Series Features

- 4,000 lb. Load Capacity
- Photo Eye
- "Easy Thread Design"
- 7" Color Touch Screen HMI
- 12 Program Memory



## Semi-Automatic Pallet Stretch Wrapper

- PLC Control with 12 Program Memory
- On/Off Switch
- Top Wrap Count
- Bottom Wrap Count
- Start/Stop
- Manual/Automatic
- Pause Button
- Film Tension Control
- Turntable Speed
- Film Carriage Speed
- Emergency Stop Switch



7" Color Touch Screen HMI

Electro-mechanical brake stretch system designed to offer up to 150% film stretch.



Heavy duty chain drive on turntable with 18 sets of double roller turntable supports.



### Technical Specifications:

- Production Rate:** 30-40 Loads Per Hour
- Power Requirements:** 110 Volts, 1 Phase, 15 Amp
- Maximum Load Size:** 50" L x 50" W x 85" H
- Maximum Load:** 4,000 lbs.
- Turntable:** 59" diameter - 3/8" Diamond Plate
- Turntable Drive:** 1/2 HP AC Variable Speed 0-12 rpm
- Turntable Drive Method:** Heavy Duty Chain ANSI #60
- Turntable Support:** Heavy Duty Delrin Roller Assembly
- Film Delivery System:** Electro-Mechanical Brake Stretch System Designed to Stretch Film up to 150%
- Machine Dimensions:** 108" L x 59" W x 102" H
- Carriage Elevator:** Variable Speed 1/2 hp - Drive Belt
- Controls:** PLC Control with 12 Program Memory
- Forklift Portable:** Yes
- Photo Eye:** Will Automatically Seek Height of Load
- Home Position:** Turntable Will Automatically Return to Home Position
- C.E. Approval:** Exceeds OSHA Safety Standards
- Film Capacity:** All Commercial Stretch Film 20" Wide
- Warranty:** 3 Year Limited Warranty
- Shipping Weight:** 1,800 lbs.

### Optional Features:

- 72" Diameter Turntable
- Tower Extension to 105"
- Base Extension of 24"
- Load Stabilizer - Top Pressure Plate
- Weight Scale Packages

